



PRODUCT SPECIFICATIONS

Model	JS1300	
THREE NUMBERS FOR THE ENGINE	Brand	WEICHAI
	Power (kw)	74 (National III) 74 (National IV)
	Number of cylinders	4
PRODUCT SPECIFICATIONS	Fuel	Diesel fuel
	Working height-full lift (A)	4390(mm)
	Bucket bottom height-full lift (C)	3220(mm)
	Total length-with bucket (E)	3805(mm)
	Flip down angle-full lift (G)	38 (°)
	Discharge distance-full lift (J)	470(mm)
	Upward inclination angle (L)	24 (°)
	Track center distance (N)	1600(mm)
	Departure angle (Q)	30 (°)
	Overall width-without bucket (S)	1920(mm)
	Turning radius-with bucket (X)	2400(mm)
	Turning radius-tail (Z)	1800(mm)
	Articulation height-full lift (B)	3440(mm)
	Height of overhead guard (D)	2130(mm)
	Overall length-without bucket (F)	3035(mm)
	Discharge height-full lift (H)	2688(mm)
	Inclination angle - full lift (K)	96 (°)
	Track ground contact length (M)	1600(mm)
	Ground clearance (P)	225(mm)
	Bucket width (R)	1880(mm)
Tail length (W)	815(mm)	
Turning radius-without bucket (Y)	1550(mm)	
HYDRAULIC ELECTRICAL SYSTEM	Standard hydraulic flow rate of attachments	85(L/min)
	Optional high hydraulic flow	135(L/min)
	Maximum oil supply pressure for accessories	21(Mpa)
	Fuel tank capacity	100(L)
	Hydraulic oil tank capacity	100(L)
	Operating voltage	DC24(V)
	Operation method	Pilot hydraulic control
BASIC TECHNICAL PARAMETERS	Rated load	1300(kg)
	Tipping load	2200(kg)
	Operating weight	4350(kg)
	Maximum driving speed	6,9(km/h)
	Tire specifications	320
	Standard bucket	72"
	Bucket width	1880(mm)
	Flat pack capacity	0.44 (m3)

ZHEJIANG JEVEDA MACHINERY CO., LTD

ADDRESS: NO.1,ROAD ONE,XINDENG NEW DISTRICT,FUYANG,HANGZHOU,ZHEJIANG 311404,CHINA

TEL:+86-571-8688 8355 (AMERICA) +86-571-8886 9363 (EUROPE) +86-571-8688 8377 (ASIA, AFRICA, OCEANIA)

E-MAIL: info@Jeveda.com