



PRODUCT SPECIFICATIONS

Model	JS800			
THREE NUMBERS FOR THE ENGINE	Brand	YANMAR		
	Power (kw)	34.6 (National III)	35.5 (National IV)	35.5(Euro 5/EPA)
	Number of cylinders	4		
	Fuel	Diesel fuel		
HYDRAULIC ELECTRICAL SYSTEM	Standard hydraulic flow rate of attachments	80(L/min)		
	Maximum oil supply pressure for accessories	21(Mpa)		
	Fuel tank capacity	80(L)		
	Hydraulic oil tank capacity	80(L)		
	Operating voltage	DC12(V)		
	Operation method	Pilot hydraulic control		
BASIC TECHNICAL PARAMETERS	Rated load	800(kg)		
	Tipping load	1600(kg)		
	Operating weight	2987(kg)		
	Maximum driving speed	12.6(km/h)		
	Tire specifications	10-16.5		
	Standard bucket	66"		
	Bucket width	1730(mm)		
	Flat pack capacity	0.4(m3)		
PRODUCT SPECIFICATIONS	Working height-full lift (A)	3970(mm)		
	Bucket bottom height-full lift (C)	2813(mm)		
	Total length-with bucket (E)	3521(mm)		
	Flip down angle-full lift (G)	39(°)		
	Discharge distance-full lift (J)	580(mm)		
	Upward inclination angle (L)	27(°)		
	Wheel base (N)	1412(mm)		
	Departure angle (Q)	22 (°)		
	Overall width-without bucket (S)	1715(mm)		
	Turning radius-with bucket (X)	2156(mm)		
	Turning radius-tail (Z)	1648(mm)		
	Articulation height-full lift (B)	3021(mm)		
	Height of overhead guard (D)	2008(mm)		
	Overall length-without bucket (F)	2763(mm)		
	Discharge height-full lift (H)	2270(mm)		
	Inclination angle - full lift (K)	96(°)		
	Wheel base (M)	1093(mm)		
	Ground clearance (P)	190(mm)		
	Bucket width (R)	1730(mm)		
Tail length (W)	991(mm)			
Turning radius-without bucket (Y)	1353(mm)			

ZHEJIANG JEVEDA MACHINERY CO., LTD

☛ ADDRESS: NO.1,ROAD ONE,XINDENG NEW DISTRICT,FUYANG,HANGZHOU,ZHEJIANG 311404,CHINA

☎ TEL:+86-571-8688 8355 (AMERICA) +86-571-8886 9363 (EUROPE) +86-571-8688 8377 (ASIA, AFRICA, OCEANIA)

✉ E-MAIL: info@Jeveda.com